

# REVERSING CAMERA OPTIONS

RÜCKFAHRKAMERA  
CAMÉRAS DE RECU



## SHARKFIN CAMERA

Part no. 0000091



- Sony CCD system offers optimum image quality
- 10m range and infra-red LEDs optimise image quality in dull and night conditions
- Reversing trigger for automatic power-up avoids battery drain

### Specifications

Image Sensor:	1/ 3" SONY
Horiz. Resolution:	420 TV lines
Lens:	F=2.5mm
Viewing Angle:	120°
Video Output:	1.0Vp-p, 75Ω
Night Vision:	9 x infra-red LEDs
Infra-red Distance:	10m
Shock Resistance:	10G
IP Rating:	IP68
Voltage:	12-24V DC (via monitor)



## REVERSING CAMERA

Part no. 0000075



- Rated to IP69K and shockproof to 10G
- 18 infra-red LEDs with a range of 13m for clear image even in dull and night conditions
- Deters potential thieves and vandals

### Specifications

Image Sensor:	1/3" Colour Sharp™ CCD
Pixels:	500 x 582 (PAL) / 510 x 492 (NTSC)
Horiz. Resolution:	700 TV lines
Lens:	f2.9mm
Viewing Angle:	120°
Video Output:	1.0Vp-p, 75Ω
Night Vision:	18 x infra-red LEDs
Infra-red Distance:	~13.5m
Shock Resistance:	10G
IP Rating:	IP69K
Voltage:	12V DC (via monitor)



## MINI-PRO CAMERA

Part no. 0000066



- Eliminated blind spots with wide-angle lens
- Enhanced low light function
- Fits anywhere with its versatile mount
- Discreet, reliable and professional

### Specifications

Image Sensor:	1/ 4" CMOS Sensor
Pixels:	720 x 576 (PAL) / 720 x 480 (NTSC)
Horiz. Resolution:	520 TV lines
Lens:	f1.9mm/ F2.0
Viewing Angle:	170° (Super Wide Angle)
Video Output:	1.0Vp-p, 75Ω
Night Vision:	Enhanced Low Light Function
Shock Resistance:	10G
IP Rating:	IP68
Voltage:	6-16V DC (via monitor)

